acer

Enlighten Your Bright Ideas Everywhere!



Acer **XD1150**



| | A VD44F0 |
|-----------------------------------|---|
| Specifications | Acer XD1150 |
| Projection System | DLP TM |
| Resolution | Native SVGA (800 x 600), Maximum SXGA (1,280 x 1,024) |
| Computer Compatibility | IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards SXGA, XGA, VGA (resizing) |
| Video Compatibility | NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), |
| | HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i) |
| Aspect Ratio | 4:3 (Native), 16:9 |
| Contrast Ratio | 2200:1 |
| Displayable Colors | 16.7 Million Colors |
| Brightness | 1,800 ANSI Lumens |
| Projection Lens | F / 2.35 ~ 2.47, f = 21.83mm ~ 23.81mm |
| • | 1:1.1 Manual Zoom and Manual Focus |
| Projection Screen Size (Diagonal) | 23.1" (0.59m) ~ 302" (7.68m) |
| Projection Distance | 3.28′ (1m) ~ 39.4′ (12m) |
| Throw Ratio | 50.4"@2m |
| Horizontal Scan Rate | 31.5 ~ 100 kHz |
| Vertical Refresh Scan Rate | 56 ~ 85 Hz |
| Lamp Type | 180 W User Replaceable SHP Lamp |
| Lamp Life | 2 000 Hours (Standard) 3 000 Hours (ECO) |
| Keystone Correction | +/-16 Degrees (Vertical) |
| Projection Mode | Front, Rear, Front-Ceiling, Rear-Ceiling |
| Ceiling Mounting Capability | Yes |
| Audio | N/A |
| Weight | 4.8 lbs (2.17Kg) |
| Dimension | 230 x 238 x 123 mm (9.1" x 9.4" x 4.8") |
| IR Remote Control | PgUp/PgDn function |
| Digital Zoom | Yes |
| Picture in Picture | N/A |
| Wireless | N/A |
| Power Supply | AC Input 100~240V auto-switching power supply |
| Power Consumption | 243 Watts (Operation), 14 Watts (Standby) |
| Operation Temperature | 5°C ~ 35°C / 41°F ~ 95°F |
| Noise Level | 31 dBA |
| Uniformity | 90% |
| Other Features | 1. Empower Key |
| | A quick button on remote control or projector control panel for user easily to perform the |
| | following three Acer unique features. |
| | 2. Acer eView Management |
| | A feature which allows user easily to select the optimal display mode for specific display content. |

A feature which allows user easily to select the optimal display mode for specific display content.

3. Acer eTimer Management

A feature which allows user to enable a Timer function during the presentation. A digit clock will be displayed on the screen while the timer is in counting. A reminder on the screen and an alarm sound will be activated when time is up.

4. Acer eOpening Management

A feature which allows user to customized their desired projector startup screen.

5. Auto Shutdown

A feature which allows the projector automatically turned off according to the setting time via OSD if the projector continuously no signal input

6. Quick Start

The projector starts projecting within 15 seconds after power button being pressed

7. Quick Shutdown

The projector shuts down within 30 seconds after power button being pressed

8. Security

A feature which enables the password control capability of the projector. It prevents the projector from unauthorized usage. Also, it reduces the possibility of the projector's being stolen

9. Quick Detection

The projector can immediately detect signal as soon as any source input to the projector. No need to waste your time to wait for the signal scanning.

10. Advanced 5-Segment Color Wheel Utilize 5-segment color wheel with additional yellow segment offering great color correctness

Computer Input:

• 1 HDB 15-Pin D-Sub (VGA/Component/HDTV)

AV Input:

• 1 HDB 15-Pin D-Sub (VGA/Component/HDTV, same as above)

• 1 Composite Video RCA Jack

• 1 S-Video Mini DIN

Output:

• 1 USB Connector for Remote Computer Control

AC Power Cord

VGA Cable (15pin D-Sub) Composite Video Cable (RCA)

Remote Control with PaUp/PaDn function

Batteries x 2 for Remote Controller

User's Guide (CD-ROM) Quick Start Card

Lens Cap Carrying Case



หลอดภาพรับประกัน 1 ปี หรือ 1,000 ชั่วโมง



I/O Connectors

Standard Accessories

บริษัท เอเซอร์ คอมพิวเตอร์ จำกัด

0-2685-4311 www.acer.co.th

191/62-63 ชั้น 16 อาคารซีที่ไอ ทาวเวอร์ ถ.รัชดาภิเษกคลองเตย กรุงเทพฯ 10110 โทรศัพท์ 0-2661-9700 โทรสาร 0-2661-9721